

PGAM 80W-100W IP30

American gauge



Product family features

- Rated input voltage: 347-480V/ac
- Input voltage range: 312-528V/ac
- THD<20%
- Operating temperature: -25°C~+55°C
- Max. case temperature: 90°C
- Protection grade: IP30
- Protections: Short circuit, overload, no-load, Over temperature protection
- Warranty: 5 years
- Application: : Linear high Bays, low Bays, Round High Bays, Strip Lights




Areas of application

- Industrial lighting



Summary



Product datasheet

Technical data

Electrical data

Product Modle	Rated Power	Input Voltage	Output Current	Output Voltage Range	Power Factor	Efficiency	Size	Certification
PGAM080C1500VSLM3	80W	347-480V	1500mA	30-42V	0.9	87%	242*61*42mm	UL
PGAM080C1600VSLM3	80W	347-480V	1600mA	30-42V	0.9	87%	242*61*42mm	UL
PGAM080C1700VSLM3	80W	347-480V	1700mA	30-42V	0.9	87%	242*61*42mm	UL
PGAM080C1800VSLM3	80W	347-480V	1800mA	30-42V	0.9	87%	242*61*42mm	UL
PGAM080C1900VSLM3	80W	347-480V	1900mA	30-42V	0.9	87%	242*61*42mm	UL
PGAM100C2000VSLM3	100W	347-480V	2000mA	30-42V	0.9	87%	242*61*42mm	UL
PGAM100C2100VSLM3	100W	347-480V	2100mA	30-42V	0.9	87%	242*61*42mm	UL
PGAM100C2200VSLM3	100W	347-480V	2200mA	30-42V	0.9	87%	242*61*42mm	UL
PGAM100C2300VSLM3	100W	347-480V	2300mA	30-42V	0.9	87%	242*61*42mm	UL
PGAM100C2350VSLM3	100W	347-480V	2350mA	30-40V	0.9	87%	242*61*42mm	UL
PGAM100C2400VSLM3	100W	347-480V	2400mA	30-40V	0.9	87%	242*61*42mm	UL

Electrical Specifications

Category	Item	Technical Norm
Input	Rated Input Voltage	347-480VAC
	Range of Input Voltage	312-528VAC
	Frequency	50/60Hz
	Input Current	≤0.35A(347VAC,full load)
	Input Power	≤115W(347VAC,full load)
	Power Factor	≥0.9(347-480VAC,full load)
	THD	<20% (347-480VAC,full load)
	No-load Power Consumption	≤3W
	inrush Current	<65A (480VAC)
	Leakage current	<0.75mA (480VAC)
output	Current Accuracy	≤±5%
	Load regulation	≤±3%
	Line regulation	≤±3%
	Max. Output Power	96W
	Started Delay Time	≤0.75S(347-480VAC,full load)
	Current Ripple	<±5% Output current

Product datasheet

Technical data


Electrical Specifications

Dimming	Dimming Type	0-10V Dimming DIM OFF
	Features	Isolation Dimming
	DIM OFF Voltage	0.6-0.8V
	DIM ON Voltage	0.7-0.9V
Protection	Short Circuit Protection	Auto Recovery
	Overload Protection	Auto Recovery
	No-load Protection	Auto Recovery
Environment	Ta/Operation Temperature	-25....+55°C
	Ts/Storage Temperature	-40....+85°C
	Tc/Enclosure Temperature	90°C
	Humidity	10%....90%RH
Construction	Connection Method	Wire
	Installation	Independent external
	Input wire specification	UL1015 18AWG 105°C 600V 单股线/ UL1569 18AWG 105°C 600V 单股线
	Output wire specification	UL1015 18AWG 105°C 300V 单股线/ UL1569 18AWG 105°C 300V 单股线
	0-10V Dimmable wire specification	UL1015 18AWG 105°C 300V 单股线/ UL1569 18AWG 105°C 300V 单股线
	Dimension	242*61*42mm
Standards	Safety Standards	Conform UL, cUL, UL8750 Class 2
	EMC Standards	Conform FCC Part 15 Class A, Compliance to EN 61547/1995+ A1/2000
Others	MTBF	300000h measured at full load, 25°C ambient temperature MIL-HDBK-217F(25°C)
	Life Time	50000h @55°C(Ta)/90°C(Tc)
	Warranty	5 years
Remark	Power supply is considered as a component and used in combination with terminal equipment, because EMC is affected by the whole set of equipment, the manufacturer of terminal equipment needs to re-emc confirm the whole set of equipment.	

Product datasheet


Technical data

Installation



Appearance information

Dimensions



Product datasheet

Appearance information

Label

The sample label



PGAM100C2400VSLM3
Input: 115W 350mA @Vin =347V PF> 0.9@full load
Output:30-40VDC 2400mA
Pout:96W 0-10V Dimming
Class 2 Power Supply For use with dry or damp location only
For Connections Use Wire Rated for at least 90°C(194° F)
Class P

CONSTANT CURRENT
Dimmable LED Driver

347-480V 50/60Hz

CAUTION
DISCONNECT LINE VOLTAGE BEFORE
INSTALLING OR REPLACING.CASE MUST
BE GROUNDED

RoHS

UL LISTED
E521467

www.pairuigroup.com.cn

Made in China


0-10V
Dimmer

Black
White

DRIVER

VIOLET (-) 0V
GREEN
BLUE (-)
RED (+)

The dimming curve



Packaging information

Carton L*W*H(mm)	Pcs/Carton	weight/Pcs(kg)	weight/Carton(kg)	Gross weight/ Carton(kg)
365*260*125	10	0.8	8	8.8