



附注:

1. 未标注R角0.2mm;
2. 电镀要求:
镍层50-100uIN,
锡层200-500uIN;
3. 最大毛边允许0.1mm;
4. 产品符合RoHS环保要求;
5. 端子平面度: 0.10mm;
6. 端子拉力: 1.5KG Min

Code No.: FAY01019

| REMARK: | | | REV. | REVISIONS REC. | DATE: |
|---|---------------|-----------------------|---|----------------|------------------|
| 1. | | | 1. | | |
| 2. | | | 2. | | |
| DRAWN BY | Yuing.yu | TOLERANCES | | ANGLE: | MODEL NAME: |
| CHECKED BY | Yong.zhan | 0<L<4 ±0.10 | | ±1° | ER11.5(4+4P)-1S |
| APPROVED BY | Xueliang.zhan | 4<L<16 ±0.20 | | UNIT: | BOBBIN MATERIAL: |
| | | 16<L<63 ±0.30 | | MM | PM6930 |
| | | Pin pitch: ±0.2 | | SCALE: | PIN MATERIAL: |
| | | Wall thickness: ±0.15 | | 2:1 | C5191 |
|  天长市富安电子有限公司 TIAN CHANG FUAN ELECTRONIC CO.,LTD TEL:+86-550-7814888 FAX:+86-550-7831133 Http: www.fuantronics.net | | |  DRAWING NO: | | UL REC. |
| | | | SMD-ER-1102 | | REV. |
| | | | DATE: | | 2018.12.10 |